

MATERIAL SAFETY DATA SHEET

Section 1 - Material Identity	
Product Name: STEREO GLAZE #1 - #4210; STEREO GLAZE #2-#4211; SEAL B- #4212; STEREO GLAZE #3 - #4215; DIAMOND CRYSTAL #4 - #4216; CLEAR COAT SEALANT -#9200	Product Use: Polishing Compound
Manufacturer(s) Supplier (s) Name & Address	Telephone Number: (215) 698-0500
ARDEX LABORATORIES, INC. 2050 BYBERRY ROAD PHILADELPHIA , PA 19116	Days: (215) 698-0500 Nights: CHEMTREC: 800/424-9300
DOT Proper Shipping Name: POLISHING COMPOUND	

Section 2 - Physical & Chemical Characteristics		
V.O.C.: 10.97% by weight (4210), 11.52% by weight (4211), 11.90% by weight (4212), 10.36% by weight (4215), 11.71% by weight (4216), 11.48% by weight (9200). OTC VOC Compliant for 2005.		
	Solubility in Water by Weight: DISPERSIBLE	Boiling Point: 300-475 DEG. F.
Appearance and Odor: CREAMY LIQUID, CHARACTERISTIC SOLVENT-FRUITY- ODOR. #4210-YELLOW, #4211-LIGHT BLUE; #4212 -GRAY; #4215 - TAN, #4216-LIGHT PURPLE; #9200-WHITE.	Specific Gravity: 0.900-1.15 (@60 DEG. F.)	Freezing Point: 25 DEG. F.
Vapor Pressure at 20EC: 2.5 (@68 DEG. F.)	Percent Volatile by Volume: <85%	Evap. Rate (Butyl Acetate=1): NEGLIGIBLE

Section 3 –Ingredients & Specifications				
Materials	%	TLV	Hazard	CAS Number
ALIPHATIC HYDROCARBON		100 ppm	COMBUSTIBLE	64742-47-8
ALIPHATIC HYDROCARBON		400 PPM	COMBUSTIBLE	8052-41-3
POLYDIMETHYLSILOXANE				63148-62-9
ALUMINUM SILICATE* * CRYSTALLINE SILICA		10mg/m3		133-2-587
WATER, FRAGRANCE				
MORPHOLINE		20 PPM	FLAMMABLE	110-91-8

Section 4 - Fire & Explosion Hazard Data
Flash Point & Method: 175 DEG. F.
Flammable Limits in Air % by volume: Lower: 1.5 Upper: 6.5
Extinguishing Media: ANY
Special Fire Fighting Procedures: N/A
Unusual Hazards: This product contains a combustible liquid. There is a possibility of producing vapor from this liquid at elevated temperatures. This vapor may be ignited by heat, sparks, flame or other sources of ignition. Vapors may travel considerable distances to a source of ignition where they may ignite flashback or explode. Vapor/air explosion hazard indoors/outdoors or in sewers. Vapors are heavier than air and may accumulate in low areas. If containers are not properly cooled, it may explode in the heat of fire.

Section 5 – Health Hazard Data	
Route of Entry	
Effects of Acute Exposure: <u>HEALTH: 2</u> <u>FLAMMABILITY: 2</u> <u>PHYSICAL HAZARD: 0</u> <u>PERSONAL PROTECTION: E</u>	a) Skin Contact: PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DRYING OF THE SKIN. b) Eye Contact: May cause stinging, tearing, redness, & swelling. c) Swallowing: May cause irritation of the digestive tract, signs of nervous system depression (E.G., headache, drowsiness, dizziness, loss of concentrations and fatigue. d) Skin Absorption: PROMPTLY WASH AFFECTED AREA WITH MILD SOAP AND WATER. REMOVE CLOTHING IF PRESENT. IF IRRITATION OR REDNESS PERSISTS GET MEDICAL ATTENTION. e) Inhalation: MOVE PERSON TO FRESH AIR AT ONCE. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP THE AFFECTED PERSON WARM AND AT REST. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.
	EXPOSURE TO HIGH CONCENTRATIONS OF THIS MATERIAL (E.G., IN ENCLOSED SPACES OR WITH

Chronic Effects of Overexposure:	DELIBERATE ABUSE) MAY BE ASSOCIATED WITH CARDIAC ARRHYTHMIAS, EPINEPHRINE AND OTHER SYMPATHOMIMETIC DRUGS MAY INITIATE CARDIAC ARRHYTHMIAS IN PERSONS EXPOSED TO THIS MATERIAL. REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Other Health Hazards:	N/A
Emergency and First Aid Procedures:	a) Skin: RINSE WITH WATER. IF IRRITATED WASH WITH MILD SOAP AND WATER. CONTACT PHYSICIAN.
	b) Eyes: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. GET MEDICAL ATTENTION.
	c) Swallowing: Do NOT induce vomiting. Give two (2) glasses of water. Contact physician
	d) Inhalation: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING IS DIFFICULT. CONTACT PHYSICIAN.

Carcinogen Evaluation: Raw Material components contained in this product are not known or suspected to be carcinogens. Proposition 65: Ethyl acrylate is known in the State of California to cause cancer. This product contains negligible trace amount of ethyl acrylate.

Section 6 - Reactivity Data

Stability -	Yes
Conditions to Avoid for Stability	See below
Incompatibility (Materials to Avoid) -	Avoid strong acids or bases, oxidizing agents & selected amines. This product forms combustible and/or explosive mixtures with air or oxygen.
Hazardous Polymerization -	Will not occur
Hazardous Decomposition/Byproducts	Carbon Monoxide and/or Carbon Dioxide.

Section 7 - Spill or Leak Procedures

Release/Spill Procedures	VENTILATE AREA. ABSORB INTO NON-REACTIVE MEDIA SUCH AS DIATOMACEOUS EARTH OR VERMICULITE; SWEEP INTO NON-REACTIVE VESSEL (I.E., STEEL DRUM OR PAIL)
--------------------------	---

Section 8 - Special Protection Information

Protective Equipment	Eyes: USE DUST-AND SPLASH-PROOF SAFETY GOGGLES WHERE THERE IS ANY POSSIBILITY OF LIQUID, MIST OR DUST CONTACTING THE EYES.
	Respirator: RECOMMENDED DUST MASK
	Gloves: WEAR IMPERMEABLE GLOVES (BUTYL OR HEAVY VINYL LATEX TYPE)
	Other: PROTECTIVE EQUIPMENT – IF POSSIBILITY EXISTS FOR SPLASHING WEAR FACEGUARDS WITH SIDE SHIELDS. USE RESPIRATOR WHEN WORKING IN A TOTALLY CLOSED SYSTEM.
Ventilation	General Mechanical: None required
	Other: USE IN A WELL VENTILATED AREA

Section 9 - Special Precautions

Handling & Storage	General: N/A
--------------------	--------------

Section 10- Other Information

The information contained herein is based on data considered accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility for personal injury or property damage to vendees, users or third parties caused by the material. We also do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Prepared By:

ARDEX LABORATORIES, INC.

New/Revision Date: 03/14/05