

# MATERIAL SAFETY DATA SHEET

| Section 1 - Material Identity   |  |
|---|--|
| Product Name <b>CITRUS BELT ALL- PURPOSE CLEANER<br/>- #6205</b>                  | Product Use: <b>Cleaning Compound</b>  |
| Manufacturer(s) Supplier (s) Name & Address                                       | Telephone Number: (215) 698-0500   |
| <b>ARDEX LABORATORIES, INC.<br/>2050 BYBERRY ROAD<br/>PHILADELPHIA , PA 19116</b> | Days:     (215) 698-0500<br>Nights:   CHEMTREC: 800/424-9300   |
| DOT Proper Shipping Name : <b>Aerosols, 2, UN 1950</b>                            | May be reclassified in the US for ground or vessel shipments<br>as : <b>ORM-D CONSUMER COMMODITY</b> |
| <b>FLAMMABLE</b>  |  |

| Section 2 - Physical & Chemical Characteristics  |  |  |
|--|--|--|
| V.O.C.: 6.00% by weight. OTC VOC Compliant for 2005.   | Solubility in Water by Weight: <b>100%</b>     | Boiling Point: <b>Concentrate Range: 212</b> |
| Appearance and Odor: <b>CONCENTRATE: AMBER LIQUID, SLIGHT CITRUS ODOR; PROPELLANT: COLORLESS, ODORLESS GAS</b> | Specific Gravity: <b>Concentrate: 0.9-1.10</b> | Freezing Point                               |
| Vapor Pressure at 20EC:  | Percent Volatile by Volume:                    | Evap. Rate (Butyl Acetate=1): >1             |

| Section 3 -Ingredients & Specifications    |   |                     |        |            |
|--|---|---------------------|--------|------------|
| Materials                                  | % | TLV                 | Hazard | CAS Number |
| ETHYLENE GLYCOL<br>Monobutyl Ether         |   | 50 ppm              |        | 111-76-2   |
| LIQUEFIED<br>PETROLEUM GAS<br>(Propellant) |   | 1000 ppm            |        | 68476-85-7 |
| SODIUM PHOSPHATE                           |   | 2 mg/m <sup>3</sup> |        | 7758-29-4  |
| d-LIMONENE                                 |   | N/A                 |        | 5989-27-5  |
| SODIUM EDTA                                |   | N/A                 |        | 10378-23-1 |

| Section 4 - Fire & Explosion Hazard Data   |
|--|
| Flash Point & Method:  |
| Flammable Limits in Air % by volume:     Lower:N/A                  Upper: N/A   |
| Extinguishing Media: <b>WATER FOG, DRY CHEMICAL, CARBON DIOXIDE</b>  |
| Special Fire Fighting Procedures: <b>WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE BURSTING WHEN EXPOSED TO HIGH TEMPERATURES. FIREMEN SHOULD WEAR SELF-CONTAINED, POSITIVE PRESSURE, RESPIRATORY EQUIPMENT.</b> |
| Unusual Hazards: <b>N/A</b>  |

| Section 5 - Health Hazard Data   |   |
|--|---|
| Route of Entry   | a) Skin b) eyes:  |
| Effects of Acute Exposure:<br><br><b><u>HEALTH:</u>                                    1</b><br><b><u>FLAMMABILITY:</u>                        0</b><br><b><u>PHYSICAL HAZARD:</u>                    0</b><br><b><u>PERSONAL PROTECTION:</u>            A</b> | a) Skin Contact: <b>PROLONGED CONTACT MAY CAUSE IRRITATION, DEFATTING OF SKIN.</b>  |
|  | b) Eye Contact: <b>CONTACT WITH LIQUID OR MIST MAY CAUSE IRRITATION, POSSIBLY PERMANENT INJURY. VAPORS MAY IRRITATE EYES.</b> |
|  | c) Swallowing: <b>ASPIRATION MAY CAUSE RAPID ABSORPTION THROUGH THE LUNGS, WHICH MAY RESULT IN SYSTEMIC EFFECTS.</b>          |
|  | d) Skin Absorption: <b>WASH OFF IN FLOWING WATER OR SHOWER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.</b>           |

|                                     |  |
|-------------------------------------|--|
| *                                   | e) Inhalation: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS OF THE CAN MAY BE HARMFUL OR FATAL.                                    |
| Chronic Effects of Overexposure:    | OVEREXPOSURE TO VAPOR MAY CAUSE DIZZINESS, LOSS OF CONCENTRATION AND IRRITATION.   |
| Other Health Hazards:               | N/A  |
| Emergency and First Aid Procedures: | a) Skin WASH OFF IN FLOWING WATER OR SHOWER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.   |
|                                     | b) Eyes: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. GET MEDICAL ASSISTANCE IF IRRITATION PERSISTS. |
|                                     | c) Swallowing: Do NOT induce vomiting. Call a physician immediately.   |
|                                     | d) Inhalation: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.                             |

### Carcinogen Evaluation - Chemical listed as Carcinogen

### Section 6 - Reactivity Data

|  |  |
|--|--|
| Stability -                            | Yes                                    |
| Conditions to Avoid for Stability      | See below                              |
| Incompatibility (Materials to Avoid) - | NONE                                   |
| Hazardous Polymerization -             | Will not occur                         |
| Hazardous Decomposition/Byproducts     | Carbon Monoxide and/or Carbon Dioxide. |

### Section 7 - Spill or Leak Procedures

|                          |  |
|--------------------------|--|
| Release/Spill Procedures | Small Spills: Remove ignition sources. Mop up, or soak up immediately. Use proper protective equipment.          |
|                          | Large Spills: Evacuate area. Remove ignition sources. Transfer to closed containers; keep out of water supplies. |

### Section 8 - Special Protection Information

|                      |  |
|----------------------|--|
| Protective Equipment | Eyes: USE DUST-AND SPLASH-PROOF SAFETY GOGGLES WHERE THERE IS ANY POSSIBILITY OF LIQUID, MIST OR DUST CONTACTING THE EYES.                                   |
|                      | Respirator: NIOSH OR BUREAU OF MINES APPROVED ORGANIC VAPOR-TYPE RESPIRATOR IS REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.                          |
|                      | Gloves: WEAR SOLVENT RESISTANT GLOVES – IMPERVIOUS GLOVES.   |
| Ventilation          | other: PROTECTIVE EQUIPMENT – IF POSSIBILITY EXISTS FOR SPLASHING WEAR FACEGUARDS WITH SIDE SHIELDS. USE RESPIRATOR WHEN WORKING IN A TOTALLY CLOSED SYSTEM. |
|                      | General Mechanical: None required  |
|                      | Other: USE IN A WELL VENTILATED AREA   |

### Section 9 - Special Precautions

|                    |   |
|--------------------|---|
| Handling & Storage | General: DO NOT STORE ABOVE 110 DEG. F. DO NOT USE OR STORE NEAR ANY OPEN FLAMES OR IGNITION SOURCES.   |
|                    | Other: CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE. EXPOSURE TO TEMPERATURES ABOVE 120 DEG. F MAY CAUSE CAN TO BURST. VAPORS ARE HEAVIER THAN AIR & WILL COLLECT IN LOW AREAS. |

### Section 10- Other Information

The information contained herein is based on data considered accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility for personal injury or property damage to vendees, users or third parties caused by the material. We also do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Prepared By:

ARDEX LABORATORIES, INC.

New/Revision Date: 03/14/05